



Panel alternatives

Tilting height

Volume net/gross

Weight

Transport package (WXDXH)

B, E

425 mm

100 litres /120 litres

290 kg

1550 x 1405 x 1200 / 350 kg

Connections:

Electric

Potable Cold water

Warm water (option)

Cold water for steam generator

House steam

Condensate

#E2 1.5 kW, 230V, 1~, 20A, 50/60 Hz

#2 G1/2", 2...8 bar

#3 G1/2", 2...8 bar

#5 G1/2", 2...8 bar, Filtered to 50 microns, Soft Max 6°dH

#6 G1/2" 1.5... 2 bar, 40 kg/h

#7 G1/2"

Options (factory installation required):

Chill CH1 - Chill CH2 - Chill CH3 - Wash hose with spray pistol - Single hand faucet C/W

Draw off valve - Energy optimization

Options:

- Strainer plate - Wash tool - Wing for dough - Whipping tool - Tool trolley - Wall bracket for mixing tools
- Cleaning Set

Head Office

131 Alexander Street
Crows Nest NSW 2065
Ph +61 2 9966 9500
Fax +61 2 9966 9511

Brisbane

Ph: 1300 138 026
Fax: +61 7 3878 9042
M: +61 411 500 245

Melbourne

Ph: 1300 138 026
Fax: 1300 138 027